



BUILDING WIDTH	UNDER TRUSS	COLUMN SIZE	M2000 "A"	M3000 "A"	"B"	"C"	ROOF PITCH
24'-0"	9'-10"	W6	22'-0"	23'-0"	1'-0"	2'-0"	15:12
	12'-14"	W6	33'-0"	23'-0"	1'-0"	2'-6"	
	16'-18"	W9	21'-0"	22'-0"	1'-0"	2'-6"	
	20'	W9	21'-0"	22'-0"	1'-0"	2'-6"	
32'-0"	9'-10"	W6	30'-0"	31'-0"	1'-0"	2'-0"	15:12
	12'-14"	W6	30'-0"	31'-0"	1'-0"	2'-6"	
	16'-18"	W8	29'-0"	30'-0"	1'-0"	2'-6"	
	20'	W9	29'-0"	30'-0"	1'-0"	2'-6"	
40'-0"	9'-10"	W6	38'-0"	39'-0"	2'-0"	2'-0"	15:12
	12'-14"	W9	37'-0"	38'-0"	2'-0"	2'-6"	
	16'-18"	W9	37'-0"	38'-0"	2'-0"	2'-6"	
	20'	W9	37'-0"	38'-0"	2'-0"	2'-6"	
50'-0"	9'-10"	W6	46'-0"	45'-0"	2'-0"	2'-6"	15:12
	12'-14"	W8	47'-0"	46'-0"	2'-6"	2'-6"	
	16'-18'-20'	W8	47'-0"	46'-0"	2'-6"	2'-6"	
60'-0"	9'-10'-12'-14"	W9	57'-0"	58'-0"	2'-6"	2'-6"	15:12
	16'-18'-20'	W9	57'-0"	58'-0"	2'-6"	2'-6"	
70'-0"	9'-10'-12'-14"	W9	67'-0"	68'-0"	3'-0"	3'-0"	15:12
	16'-18'-20'	W10	67'-4"	68'-4"	3'-0"	3'-0"	
80'-0"	9'-10'-12'-14"	W9	77'-0"	78'-0"	3'-0"	3'-0"	15:12
	16'-18'	W10	77'-4"	78'-4"	3'-0"	3'-0"	
	20'	W10	77'-4"	78'-4"	3'-0"	3'-0"	

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING