



BUILDING WIDTH	EAVE	"A"	"B"	"C"	"D"	"E"	"F"	ROOF PITCH
20'-0"	8'-10'-12'-14'	19'-0"	18"	16'-0"	2'-4 1/2"	9"	8"	3:12
24'-0"	8'-10'-12'-14'-16'	23'-0"	18"	20'-0"	2'-10 1/2"	9"	8"	3:12
32'-0"	8'-10'-12'-14'-16'-18'	31'-0"	21"	27'-6"	3'-10 1/2"	9"	8"	3:12
40'-0"	8'-10'-12'-14'-16'-18'	39'-0"	24"	35'-0"	4'-10 1/2"	9"	8"	3:12
50'-0"	8'-10'-12'-14'-16'-18'-20'	49'-0"	27"	44'-6"	6'-1 1/2"	9"	8"	3:12
60'-0"	8'-10'-12'-14'-16'-18'-20'	59'-0"	36"	53'-0"	7'-4 1/2"	9"	8"	3:12
70'-0"	8'-10'-12'-14'-16'-18'-20'	69'-0"	42"	62'-0"	8'-7 1/2"	9"	8"	3:12
80'-0"	8'-10'-12'-14'-16'-18'-20'	79'-0"	42"	72'-0"	9'-10 1/2"	9"	8"	3:12
100'-0"	10'-12'-14'-16'-18'-20'	99'-0"	60"	89'-0"	12'-4 1/2"	12"	12"	3:12
120'-0"	12'-14'-16'-18'-20'	119'-0"	72"	107'-0"	14'-10 1/2"	18"	18"	3:12

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING