



BUILDING WIDTH	UNDER TRUSS	COLUMN SIZE	"A"	"B"	"C"	"D"	"E"	ROOF PITCH
24'-0"	8'-10"	W6	23'-0"	2'-5 1/2"	4'-0"	6'-4"	2'-4"	4.0:12
	12'-14"	W6	23'-0"	2'-5 1/2"	4'-0"	6'-4"	2'-4"	
	16'-18"	W8	22'-8"	2'-5 1/2"	4'-0"	6'-4"	2'-4"	
	20'	W8	22'-8"	2'-5 1/2"	4'-0"	6'-4"	2'-4"	
32'-0"	8'-10"	W8	10'-8"	1'-4 1/16"	5'-4"	8'-6"	1'-2"	4.0:12
	12'-14"	W8	10'-8"	1'-4 1/16"	5'-4"	8'-6"	1'-2"	
	16'-18"	W8	10'-8"	1'-4 1/16"	5'-4"	8'-6"	1'-2"	
	20'	W8	10'-8"	1'-4 1/16"	5'-4"	8'-6"	1'-2"	
40'-0"	8'-10"	W8	18'-8"	4'-2 5/8"	6'-8"	10'-8"	4'-0"	4.0:12
	12'-14"	W8	18'-8"	4'-2 5/8"	6'-8"	10'-8"	4'-0"	
	16'-18"	W8	18'-8"	4'-2 5/8"	6'-8"	10'-8"	4'-0"	
	20'	W8	18'-8"	4'-2 5/8"	6'-8"	10'-8"	4'-0"	
50'-0"	8'-10"	W8	48'-8"	5'-1 1/4"	8'-4"	13'-4"	5'-0"	4.0:12
	12'-14"	W10	48'-4"	5'-1 1/4"	8'-4"	13'-4"	5'-0"	
	16'-18'-20"	W10	48'-4"	5'-1 1/4"	8'-4"	13'-4"	5'-0"	
60'-0"	8'-10'-12'	W10	58'-4"	6'-1 7/8"	10'-0"	16'-0"	6'-0"	4.0:12
	14'-16'-18'-20"	W12	58'-0"	6'-1 7/8"	10'-0"	16'-0"	6'-0"	
70'-0"	8'-10'-12'	W12	68'-0"	7'-4 9/16"	11'-8"	18'-8"	7'-0"	4.0:12
	14'-16'-18'-20"	W14	67'-8"	7'-4 9/16"	11'-8"	18'-8"	7'-0"	
80'-0"	8'-10'-12'	W14	77'-8"	7'-10 7/8"	11'-4"	20'-10"	7'-6"	4.0:12
	14'-16'-18"	W18	77'-0"	7'-10 7/8"	11'-4"	20'-10"	7'-6"	
	20'	W18	77'-0"	7'-10 7/8"	11'-4"	20'-10"	7'-6"	

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING