



BUILDING WIDTH	UNDER TRUSS	COLUMN SIZE	'A'	'B'	'C'	'D'	ROOF PITCH
24'-0"	8'-10'	W6	23'-0"	5'	3'-0"	2'-0"	3:12
	12'-14'	W6	23'-0"	5'	3'-0"	4'-0"	
	16'-18'	W8	22'-8"	5'	3'-0"	4'-0"	
	20'	W8	22'-8"	5'	3'-0"	4'-0"	
32'-0"	8'-10'	W6	31'-0"	5'	4'-0"	2'-0"	3:12
	12'-14'	W6	31'-0"	5'	4'-0"	4'-0"	
	16'-18'	W8	30'-8"	5'	4'-0"	4'-0"	
	20'	W8	30'-8"	5'	4'-0"	4'-0"	
40'-0"	8'-10'	W6	39'-0"	5'	5'-0"	2'-0"	3:12
	12'-14'	W8	38'-8"	5'	5'-0"	4'-0"	
	16'-18'	W8	38'-8"	5'	5'-0"	4'-0"	
	20'	W8	38'-8"	5'	5'-0"	4'-0"	
50'-0"	8'-10'	W6	49'-0"	5'	6'-3"	4'-0"	3:12
	12'-14'	W8	48'-8"	5'	6'-3"	4'-0"	
	16'-18'-20'	W8	48'-8"	5'	6'-3"	4'-0"	
60'-0"	8'-10'-12'-14'-16'-18'	W8	58'-8"	5'	7'-5"	4'-0"	2.967:12
	20'	W8	58'-8"	5'	7'-5"	4'-0"	
70'-0"	8'-10'-12'-14'-16'	W8	68'-8"	5'	7'-5"	4'-0"	2.543:12
	18'-20'	W10	68'-4"	5'	7'-5"	4'-0"	
80'-0"	8'-10'-12'-14'	W8	78'-8"	5'	7'-5"	4'-0"	2.225:12
	16'-18'	W10	78'-4"	5'	7'-5"	4'-0"	
	20'	W10	78'-4"	5'	7'-5"	4'-0"	

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING