



BUILDING WIDTH	UNDER TRUSS	COLUMN SIZE	"A"	"B"	"C"	"D"	ROOF PITCH
24'-0"	8'-10'	W6	23'-0"	2'-0"	1'-0"	3'-0"	0.5:12
	12'-14'	W6	23'-0"	2'-0"	1'-0"	3'-0"	
	16'-18'	WB	22'-8"	2'-0"	1'-0"	3'-0"	
	20'	WB	22'-8"	2'-0"	1'-0"	3'-0"	
32'-0"	8'-10'	W6	31'-0"	2'-6"	1'-4"	3'-10"	0.5:12
	12'-14'	W6	31'-0"	2'-6"	1'-4"	3'-10"	
	16'-18'	WB	30'-8"	2'-6"	1'-4"	3'-10"	
	20'	WB	30'-8"	2'-6"	1'-4"	3'-10"	
40'-0"	8'-10'	W6	39'-0"	3'-2"	1'-8"	4'-10"	0.5:12
	12'-14'	WB	38'-8"	3'-2"	1'-8"	4'-10"	
	16'-18'	WB	38'-8"	3'-2"	1'-8"	4'-10"	
	20'	WB	38'-8"	3'-2"	1'-8"	4'-10"	
50'-0"	8'-10'	W6	49'-0"	3'-11"	2'-1"	6'-0"	0.5:12
	12'-14'	WB	48'-8"	3'-11"	2'-1"	6'-0"	
	16'-18'-20'	WB	48'-8"	3'-11"	2'-1"	6'-0"	
60'-0"	8'-10'-12'-14'-16'-18'	WB	58'-8"	4'-9"	2'-6"	7'-3"	0.5:12
	16'-18'-20'	WB	58'-8"	4'-9"	2'-6"	7'-3"	
70'-0"	8'-10'-12'-14'-16'	WB	68'-8"	4'-6"	2'-11"	7'-5"	0.5:12
	18'-20'	W10	68'-4"	4'-6"	2'-11"	7'-5"	
80'-0"	8'-10'-12'-14'	WB	78'-8"	4'-1'	3'-4"	7'-5"	0.5:12
	16'-18'	W10	78'-4"	4'-1'	3'-4"	7'-5"	
	20'	W10	78'-4"	4'-1'	3'-4"	7'-5"	

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING