



BUILDING WIDTH	UNDER TRUSS	COLUMN SIZE	"A"	"B"	"C"	ROOF PITCH
24'-0"	8'-10'-12'-14'-16'	W6	23'-0"	1'-0"	3'-0"	2:12
	18'	W6	23'-0"	1'-0"	3'-0"	
	20'	WB	22'-8"	1'-0"	3'-0"	
32'-0"	8'-10'-12'-14'-16'	W6	31'-0"	2'-0"	4'-8"	2:12
	18'	W6	31'-0"	2'-0"	4'-8"	
	20'	WB	30'-8"	2'-0"	4'-8"	
40'-0"	8'-10'-12'-14'	W6	39'-0"	2'-0"	5'-4"	2:12
	16'-18'	WB	38'-8"	2'-0"	5'-4"	
	20'	WB	38'-8"	2'-0"	5'-4"	
50'-0"	8'-10'-12'-14'	W6	49'-0"	2'-4"	6'-6"	2:12
	16'-18'	WB	48'-8"	2'-4"	6'-6"	
	20'	WB	48'-8"	2'-4"	6'-6"	
60'-0"	8'-10'-12'-14'-16'	WB	58'-8"	2'-6"	7'-6"	2:12
	18'-20'	WB	58'-8"	2'-6"	7'-6"	
70'-0"	8'-10'-12'-14'	WB	68'-8"	2'-9"	7'-9"	1.75:12
	16'-18'-20'	WB	68'-8"	2'-9"	7'-9"	
80'-0"	8'-10'-12'-14'-16'	WB	78'-8"	3'-0"	7'-9"	1.425:12
	18'-20'	V10	78'-4"	3'-0"	7'-9"	
100'-0"	8'-10'-12'-14'-16'-18'	V10	98'-4"	3'-0"	7'-9"	1.14:12
	20'	V10	98'-4"	3'-0"	7'-9"	
120'-0"	8'-10'-12'-14'-16'-18'	V10	118'-4"	3'-0"	7'-9"	0.95:12
	20'	W12	118'-0"	3'-0"	7'-9"	

ABOVE SPECIFICATIONS ARE BASED ON PERKA'S STANDARD LIVE LOAD AND BAY SPACING